

Table of Contents

Preface.....	7
Introduction.....	9
1. Scope.....	13
2. References.....	13
2.1 HART Documents	13
2.2 Related Documents	13
2.3 Data Link Layer - Physical Layer Interface.....	14
3. Definitions	14
4. Symbols and Abbreviations	15
5. Physical Device Types.....	16
6. Network Configuration Rules.....	16
7. Common C8PSK Characteristics.....	16
7.1 FSK Compatibility	18
7.1.1 PSK / FSK Characters.....	18
7.2 Transmitter Requirements.....	18
7.2.1 Digital Signaling Requirements.....	18
7.2.2 Data Flow.....	19
7.2.3 Scrambler	19
7.2.4 Phase Mapping.....	19
7.3 Operating Sequence	21
7.3.1 Turn-On Sequence	21
7.3.2 Frame Transmission.....	21
7.3.3 Turn-Off Sequence.....	22
7.4 Receiver Requirements	22
7.4.1 Carrier Detect.....	22
7.4.2 FSK/ C8PSK Mode Selection.....	22
7.4.3 Automatic Gain Control.....	22
7.4.4 Symbol Synchronization.....	22
7.4.5 Phase Lock Loop.....	22
7.4.6 Channel Compensation	23
7.4.7 Equalization	23

7.4.8	Symbol Unmapping	23
7.4.9	Descrambler	23
7.4.10	End of Message	23
7.5	Response Times	23
7.5.1	Carrier Start up Time	23
7.5.2	Carrier Detect Activation	23
7.5.3	Detection of Signaling Mode	24
7.5.4	Carrier Stop Time	24
7.5.5	Carrier Detect Deactivation	25
7.6	Analog Signaling Requirements	25
7.7	Other Characteristics	25
7.8	Test Loads	25
8.	Non Communicating Network Devices	25
ANNEX A.	Revision History	26
A1.	Revision 1.0	26